NANOLEX MATTE FINAL FINISH

Page: 1 Compilation date: 06.12.2019

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: NANOLEX MATTE FINAL FINISH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: Infinitec GmbH

Matzenberg 171 Saarbrücken D-66115 Germany Tel: +4968198 800306

Email: a.neuner@infinitec-gmbh.de

1.4. Emergency telephone number

Emergency tel: Medical Emergency information in case of poisoning: Poison Information Center Mainz -

24h - Phone: +49 (0) 6131 19240 (advisory service in German or English language)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

| Classification under CLP: | Eye Irrit. 2: H319 |
|---------------------------|--------------------|
|---------------------------|--------------------|

Most important adverse effects: Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H319: Causes serious eye irritation. Hazard pictograms: GHS07: Exclamation mark



| Signal words: | Warning |
|---------------------------|-------------------------------------------------------------------------------------|
| Precautionary statements: | P264: Wash hands thoroughly after handling. |
| | P280: Wear protective gloves/protective clothing/eye protection/face protection. |
| | P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove |
| | contact lenses, if present and easy to do. Continue rinsing. |
| | P337+P313: If eye irritation persists: Get medical advice/attention. |
| | P101: If medical advice is needed, have product container or label at hand. |

NANOLEX MATTE FINAL FINISH

Page: 2

P102: Keep out of reach of children.

P501: Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETIC ACID

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|---------|-----------|--------------------------------------------|---------|
| 200-580-7 | 64-19-7 | - | Flam. Liq. 3: H226; Skin Corr. 1A: H314 | 1-10% |

2-BUTOXYETHANOL

| 203-905-0 | 111-76-2 | - | Acute Tox. 4: H332; Acute Tox. 4: H312; | 1-10% |
|-----------|----------|---|-----------------------------------------|-------|
| | | | Acute Tox. 4: H302; Eye Irrit. 2: H319; | |
| | | | Skin Irrit. 2: H315 | |

COCAMIDOPROPYL BETAINE

| - | 61789-40-0 | - | Eye Dam. 1: H318; Aquatic Acute 1: | <1% |
|---|------------|---|------------------------------------|-----|
| | | | H400; Aquatic Chronic 3: H412 | |

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

examination.

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

NANOLEX MATTE FINAL FINISH

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing - see section

8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

NANOLEX MATTE FINAL FINISH

Hazardous ingredients:

2-BUTOXYETHANOL

Workplace exposure limits:

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK | 25 ppm | 50 ppm | - | - |

Respirable dust

DNEL/PNEC Values

Hazardous ingredients:

2-BUTOXYETHANOL

| Туре | Exposure | Value | Population | Effect |
|------|---------------------------------------|------------|------------|----------|
| DNEL | Inhalation | 246 mg/m | Workers | Local |
| DNEL | Inhalation | 89 mg/kg | Workers | Systemic |
| DNEL | Inhalation | 1,091 mg/m | Workers | Systemic |
| DNEL | Inhalation | 125 mg/kg | Workers | Systemic |
| DNEL | Inhalation | 98 mg/m | Workers | Systemic |
| PNEC | Fresh water | 8,8 mg/l | - | - |
| PNEC | Marine water | 0,88 mg/l | - | - |
| PNEC | Microorganisms in sewage treatment | 463 mg/l | - | - |
| PNEC | Soil (agricultural) | 2,33 mg/kg | - | - |

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: White

Odour: Characteristic odour

Flash point°C: 60 - 93

VOC g/l: 35

9.2. Other information

Other information: No data available.

pH: 2,8

NANOLEX MATTE FINAL FINISH

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETIC ACID...100%

| IVN | MUS | LD50 | 525 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 3310 | mg/kg |

2-BUTOXYETHANOL

| IVN | RAT | LD50 | 307 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 1230 | mg/kg |
| ORL | RAT | LD50 | 470 | mg/kg |

COCAMIDOPROPYL BETAINE

| DERMAL | RBT | LD50 | >2000 | mg/kg |
|--------|-----|------|-------|-------|
| ORAL | RAT | LD50 | 2335 | mg/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|-------------------------------|-------|-----------------------|
| Serious eye damage/irritation | OPT | Hazardous: calculated |

NANOLEX MATTE FINAL FINISH

| | | | Pa | ige: 6 | |
|--------------------------------|----------------------------------------------------------------------------------|--------------------------|----------------|---------------|--|
| Symptoms / routes of exposit | re | | | | |
| Skin contact: | There may be irritation and redness at the site | e of contact. | | | |
| Eye contact: | There may be pain and redness. The eyes may water profusely. There may be severe | | | | |
| | pain. The vision may become blurred. May ca | use permanent dama | ge. | | |
| Ingestion: | There may be soreness and redness of the m | outh and throat. Naus | ea and stomach | | |
| | pain may occur. | | | | |
| Inhalation: | There may be irritation of the throat with a fee | ling of tightness in the | chest. | | |
| Delayed / immediate effects: | Immediate effects can be expected after shor | -term exposure. | | | |
| Section 12: Ecological inforr | ation | | | | |
| 40.4 Taulallu | | | | | |
| 12.1. Toxicity | | | | | |
| Hazardous ingredients: | | | | | |
| COCAMIDOPROPYL BETA | NE | | | | |
| FISH | 96H LC50 | 472-500 | mg/l | | |
| | 00112000 | 472 000 | ing/i | | |
| 12.2. Persistence and degrac | ability | | | | |
| Persistence and degradability: | Biodegradable. | | | | |
| 12.3. Bioaccumulative potent | al | | | | |
| Bioaccumulative notential: | No bioaccumulation potential. | | | | |
| 12.4. Mobility in soil | | | | | |
| | | | | | |
| Mobility: | Readily absorbed into soil. | | | | |
| 12.5. Results of PBT and vPv | 3 assessment | | | | |
| PBT identification: | This product is not identified as a PBT/vPvB s | ubstance. | | | |
| 12.6. Other adverse effects | | | | | |
| Other adverse effects: | Negligible ecotoxicity | | | | |
| | · · · | | | | |
| Section 13: Disposal conside | Tations | | | | |
| 13.1. Waste treatment metho | s | | | | |
| Disposal operations: | Transfer to a suitable container and arrange f | or collection by specia | lised disposal | | |
| | company. | | | | |
| NB: | The user's attention is drawn to the possible e | xistence of regional o | r national | | |
| | regulations regarding disposal. | | | | |
| Section 14: Transport inform | ation | | | | |
| | This product does not require a classification | for transport | | | |
| Transport class: | mis product does not require a classification | | | | |

Section 15: Regulatory information

NANOLEX MATTE FINAL FINISH

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

| Other information | |
|------------------------------|------------------------------------------------------------------------------------------|
| Other information: | This safety data sheet is prepared in accordance with Commission Regulation (EU) No |
| | 2015/830. |
| | * indicates text in the SDS which has changed since the last revision. |
| Phrases used in s.2 and s.3: | H226: Flammable liquid and vapour. |
| | H302: Harmful if swallowed. |
| | H312: Harmful in contact with skin. |
| | H314: Causes severe skin burns and eye damage. |
| | H315: Causes skin irritation. |
| | H318: Causes serious eye damage. |
| | H319: Causes serious eye irritation. |
| | H332: Harmful if inhaled. |
| | H400: Very toxic to aquatic life. |
| | H412: Harmful to aquatic life with long lasting effects. |
| Legal disclaimer: | The above information is believed to be correct but does not purport to be all inclusive |
| | and shall be used only as a guide. This company shall not be held liable for any |
| | damage resulting from handling or from contact with the above product. |
| | |